

V1405-11SHBP-IR

INDOOR/ OUTDOOR POE IR CAMERA HOUSING

Infinova[®]



FEATURES

- Smart uniform irradiation solution improves image quality & monitoring effect
- Leading IR technology provides high efficiency and long-life span of LED
- Accurate constant circuit drive develops excellent performance of product
- Power and day/night switch manually controlled
- Fill light for night vision camera
- Indoor/outdoor use, all-weather use.
- High integrated solution for easy installation and saving cost

Side opening aluminium housing V1405-11SHBP-IR have been designed and manufactured to protect cameras against water and dust present in the atmosphere. The housings have been produced using highest quality aluminium materials.

TECHNICAL SPECIFICATIONS

Electrical	
Input Voltage	PoE
Output Voltage	DC12V 800mA
Power Consumption	20W
Quantity of LED	10PCS 2W IR LED
Wavelength	850nm
Beam Angle	15°/30°/45°/60° (optional)
IR Distance	80m/90m/120m/160m
Day/night Switch	Light-dependent control
Physical	
Panel	Tempered glass panel

Housing	Anti-riot PC materials
Bracket	Bottom mount bracket
Packing Dimension	482*225*170mm
Unit Weight	7.27 lbs. (3.3kg)
Shipping Weight	8.48 lbs. (3.85kg)
Environmental	
Cooling	Air cooling internal circulation
Blower	Included
Working Temperature	-40°C to +60°C (-50°C to +60°C with heater)
Protection Level	IP66
Color	White
Certifications and Approval	
Product Certifications	CE, FCC, IK10, IP66, NEMA4x

ORDERING INFORMATION

V1405-11SHBP-IR1	IR Camera housing, indoor/outdoor, 15° beam angle, 160m IR distance, IP66, PoE
V1405-11SHBP-IR2	IR Camera housing, indoor/outdoor, 30° beam angle, 120m IR distance, IP66, PoE
V1405-11SHBP-IR3	IR Camera housing, indoor/outdoor, 45° beam angle, 90m IR distance, IP66, PoE
V1405-11SHBP-IR4	IR Camera housing, indoor/outdoor, 60° beam angle, 80m IR distance, IP66, PoE

DIMENSIONS

